




Lido

037, price group 2


Somewhere in the middle between coarse and soft this high quality fabric feels comfortably welcoming. Lido is a fine weave upholstery fabric which is stain resistant and has a slight sheen to it. This fabric presents density of color very well and looks glamorous which makes it a popular choice. As furniture upholstery it gives any interior a very hospitable feel.



100% Polyester



Martindale: 105.000



Lightfastness: 6

PRODUCT CHARACTERISTICS

Product group	polyester
Applications	sofas, chairs with fitted and loose fitting upholstery
Composition faceside	100% Polyester
Composition upside	100% Polyester
Bonding	T/C
Dyeing method	piece dyed
Oeko-Tex Certificate No:	13.HCN.35063
Available colours	14



LIFESTYLE
FURNITURE
SINCE 1978

DURABILITY SPECIFICATIONS

Test	Test specification	Unit	Test result	
			Dry	Wet
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	cycles	115,000	
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	grade	4 (5)	
Colour fastness to light	DIN EN ISO 105-BO2:2014-11.	grade	6	
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11	grade	4-5 (5)	4-5 (5)
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source O: cigarette.		passed	

PROCESSING SPECIFICATION

Minimum workable width [cm]	± 148			
Roll length [m]	± 30			
Material weight [g/m]	± 485			
Test	Test specification	Unit	Test result	
			Warp	Weft
Tensile strength	DIN EN ISO 13934-1:2013-08	Newton	1900	1500
Tear strength	DIN EN ISO 13937-3:2000-06	Newton	>63	>63
Dimensional change	DIN EN ISO 5077	%	-0,2	-0,5
			Staining, multifibre	Change of colour
Colour fastness to waterwash	DIN EN ISO 105-C06	grade	4-5	4-5
Colour fastness to perspiration	DIN EN ISO 105-E04	grade	4-5	4-5
Colour fastness to dry cleaning	SS-EN ISO 105-D01	grade	4-5	4-5
Colour fastness to water spotting	SS-EN ISO 105-E16	grade	-	4,5
			Length	Width
Seam slippage	SS-EN ISO 105-B02 Alt. SS-EN 13936-3	mm	2	2
Shrinkage		%	-1,5	-2

CLEANING SPECIFICATIONS



- It is essential to wash the cover inside out and immediately place the cover back to the piece of furniture slightly damp after washing.
- Please note that during washing the damp and dirt prevention treatment will disappear faster.
- Dirt and damp prevention treatment applied.

All information is based on the data provided by the manufacturer.