




KE
BE
LIFESTYLE
FURNITURE
SINCE 1978

Lodge

551, price group 2


Lodge is a bouclé upholstery fabric with a robust yet elegant character. Its dobby-woven structure combines irregular bouclé and flat yarns, creating depth and a lively surface. Yarn-dyed for a rich appearance, Lodge offers durability and easy maintenance, while natural hairiness may occur over time and can be easily removed.



100% Polyester



Martindale: >100.000



Lightfastness: 5

PRODUCT CHARACTERISTICS

Product group	jacquard
Applications	sofas, beds, chairs with fitted and loose fitting upholstery
Composition faceside	100%PES
Composition backside	n/a
Coating	needle punch
Statistic code	54075300
Dyeing method	yarn dyed
Available colours	9



DURABILITY SPECIFICATIONS

Test	Test specification	Unit	Test result	
			Dry	Wet
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	cycles	>100.000	
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	grade	4	
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5			
	light colours	grade	5	
	middle colours	grade	5	
	dark colours	grade	5	
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11			
	light colours	grade	5	5
	middle colours	grade	4-5	5
	dark colours	grade	4-5	5
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette.			passed

PROCESSING SPECIFICATION

Minimum workable width [cm]	± 138			
Roll length [m]	± 40			
Material weight [g/m]	± 550			
Test	Test specification	Unit	Test result	
			Warp	Weft
Tensile strength	DIN EN ISO 13934-1:2013-08	Newton	1.320	751
Tear growth resistance	DIN EN ISO 13937-3:2000-06	Newton	116.5	153.9
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07 Load 180 N	mm	3.3	2.9

CLEANING SPECIFICATIONS



We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.