




# Stella

**626**, price group 2


Stella is a soft, plush upholstery fabric with a refined and inviting character. Its chenille pile structure adds volume and depth, while a subtle sheen gently reflects the light and enhances the richness of the colour. Natural pressure marks may appear over time, a characteristic of chenille fabrics that can be refreshed by light brushing.



100% Polyester



Martindale: >100.000



Lightfastness: 5

| PRODUCT CHARACTERISTICS |  |
|-------------------------|--|
| Product group           | chenille jacquard  |
| Applications            | sofas, beds, chairs with fitted and loose fitting upholstery |
| Composition faceside    | 100% PES   |
| Composition backside    | n/a  |
| Coating                 | sbr  |
| Statistic code          | 58013600   |
| Dyeing method           | piece dyed   |
| Available colours       | 8  |



| DURABILITY SPECIFICATIONS           |   |        |             |     |
|-------------------------------------|---|--------|-------------|-----|
| Test                                | Test specification  | Unit   | Test result |     |
|                                     |   |        | Dry         | Wet |
| Abrasion resistance - yarn breakage | DIN EN ISO 12947-1:2007-04,<br>DIN EN ISO 12947-2:2017-03   | cycles | >100.000    |     |
| Pilling                             | DIN EN ISO 12945-2:2000-11.<br>2000 cycles  | grade  | 4-5         |     |
| Colour fastness to light            | DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5   |        |             |     |
|                                     | light colours   | grade  | 5           |     |
|                                     | middle colours  | grade  | 5           |     |
|                                     | dark colours  | grade  | 5           |     |
| Colour fastness to rubbing          | DIN EN ISO 105-X12:2016-11  |        |             |     |
|                                     | light colours   | grade  | 5           | 5   |
|                                     | middle colours  | grade  | 5           | 5   |
|                                     | dark colours  | grade  | 4-5         | 4-5 |
| Ignitability (cigarette test)       | BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette. |        | passed      |     |

| PROCESSING SPECIFICATION    |                                       |        |             |       |
|-----------------------------|---------------------------------------|--------|-------------|-------|
| Minimum workable width [cm] | ± 138                                 |        |             |       |
| Roll length [m]             | ± 25                                  |        |             |       |
| Material weight [g/m]       | ± 828                                 |        |             |       |
| Test                        | Test specification                    | Unit   | Test result |       |
|                             |                                       |        | Warp        | Weft  |
| Tensile strength            | DIN EN ISO 13934-1:2013-08            | Newton | 1.268       | 1.123 |
| Tear growth resistance      | DIN EN ISO 13937-3:2000-06            | Newton | 75,9        | 91,5  |
| Resistance to seam slippage | DIN EN ISO 13936-2:2004-07 Load 180 N | mm     | 2,3         | 1,3   |

| CLEANING SPECIFICATIONS |  |
|-------------------------|--|
|                         | <p>We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.</p> |