




KE
BE
LIFESTYLE
FURNITURE
SINCE 1978

Avente

632, price group 3


Avente is a jacquard-woven upholstery fabric with a rich and authentic character. Its heavy, yarn-dyed structure combines virgin and recycled yarns, offering depth, durability, and a timeless look. A subtle finish adds body and stability while preserving a soft handfeel.



42% RPP, 29% PES,
26% PAC, 3% CO



Martindale: 50.000



Lightfastness: 4-5

PRODUCT CHARACTERISTICS

Product group	jacquard
Applications	sofas, beds, chairs with fitted and loose fitting upholstery
Composition faceside	42%RPP 29%PES 26%PAC 3%CO
Composition backside	n/a
Coating	sbr
Statistic code	54077200
Dyeing method	yarn dyed
Available colours	3



DURABILITY SPECIFICATIONS

Test	Test specification	Unit	Test result	
			Dry	Wet
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	cycles	50.000	
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	grade	4-5	
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5			
	light colours	grade	4-5	
	middle colours	grade	4-5	
	dark colours	grade	4-5	
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11			
	light colours	grade	4	3-4
	middle colours	grade	4	3-4
	dark colours	grade	4	3-4
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette.		passed	

PROCESSING SPECIFICATION

Minimum workable width [cm]	± 138			
Roll length [m]	± 20			
Material weight [g/m]	± 1022			
Test	Test specification	Unit	Test result	
Tensile strength	DIN EN ISO 13934-1:2013-08	Newton	1.090	550
Tear growth resistance	DIN EN ISO 13937-3:2000-06	Newton	270,0	240,0
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07 Load 180 N	mm	3,8	3,4

CLEANING SPECIFICATIONS



We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.