# Cayenne

614, price group 2

Cayenne is a mélange upholstery fabric with a distinctive, roughly woven structure and a rich, multicoloured appearance. Its yarn-dyed construction adds depth and visual character, making it a bold and durable choice for upholstery. Natural hairiness may occur over time, a characteristic of the fabric that can be easily removed without affecting its quality.

100% Polyester

Martindale: >100.000

Lightfastness: 5

PRODUCT CHARACTERISTICS

Product group	flatweave
Applications	sofas, beds, chairs with fitted and loose fitting upholstery
Composition faceside	100%PES
Composition backside	n/a
Coating	transparent
Statistic code	54075300
Dyeing method	yarn dyed
Available colours	5

KEBE
LIFESTYLE FURNITURE
SINCE 1978

DURABILITY SPECIFICATIONS

Test	Test specification	Unit	Test result	
			Dry	Wet
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	cycles	>100.000	
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	grade	4-5	
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5			
	light colours	grade	5	
	middle colours	grade	5	
	dark colours	grade	5	
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11			
	light colours	grade	5	5
	middle colours	grade	5	5
	dark colours	grade	5	5
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette.		passed	

PROCESSING SPECIFICATION

Minimum workable width [cm]	± 142
Roll length [m]	± 35
Material weight [g/m]	± 680

Test	Test specification	Unit	Test result	
			Warp	Weft
Tensile strength	DIN EN ISO 13934-1:2013-08	Newton	1.008	445
Tear growth resistance	DIN EN ISO 13937-3:2000-06	Newton	173,8	119,4
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07 Load 180 N	mm	1,0	2,0

CLEANING SPECIFICATIONS

We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

All information is based on the data provided by the manufacturer.